

## SUBMERSIBLE PUMP

VN-120 (120W)

VN-150 (150W)

VN-400 (400W)

### Features

- Portable, Save electricity and High-performance.
- Auto suction pump with cylindrical floater, easy to install in the confined spaces.
- Italy imported double-faced mechanical seal to ensure the pump seal performance.
- SUS304 stainless steel for motor housing, motor shaft and screws.
- Current protector and thermal protector.

### Application

- Suitable for clean water, salt water, factory sewage.
- Water supply and disposal, water circulation and water change for crop farming, forestry and fishery use.
- Equipment use for aquarium, landscape waterfall, water drainage and filtration.



VN-120A  
VN-150A  
VN-400A

VN-120  
VN-150  
VN-400

Model	Output Power		Caliber	Phase	Polarity	apacitor	Capacity	Head	Length	Width	Height	Weight	Max. Solids
	HP	Watt	Inch	$\phi$	P	$\mu\text{f}$	L/min	m	cm	cm	cm	kg	mm
VN-120	0.15	120	2"	1	2	10	200	4.5	25	15	38	6.6	25
VN-120A	0.15	120	2"	1	2	10	200	4.5	25	18	38	6.8	25
VN-150	0.2	150	2"	1	2	28	250	5.5	25	15	38	7.1	25
VN-150A	0.2	150	2"	1	2	28	250	5.5	25	18	38	7.3	25
VN-400	0.54	400	2"	1	2	14	360	9.6	25	18	40	8.5	25
VN-400A	0.54	400	2"	1	2	14	360	9.6	25	18	40	8.7	25

### Performance Curve

